

<i>FeelSafe IG Product Type</i>	<i>Sizes/Configurations Approved</i>	<i>DP Rating</i>	<i>Approval #</i>	<i>Glazing Options</i>
H3 2.0 FeelSafe 1-Wide or 2-Wide Casement Operators (This product NOT approved for use in Dade County)	36"x84" (Qualifies Multi-Wide) Requires 1/4" Alum Vertical Mull Plate and Mull Clips	+50-60 Wind Zone 3, Missile Level D	436-H-660.82 FL21966.4 & 23008	Type MM
H3 2.0 FeelSafe 3-Wide Casement Operators (This product NOT approved for use in Dade County)	106"x72" (36x72 Call Out) (Qualifies 1-Wide, 2-Wide, 3-Wide) Requires Mull Clips	+50-60 Wind Zone 3, Missile Level D	436-H-660.70 FL21966.1 & 23008	Type LL or Type NN
H3 2.0 FeelSafe Casement Operator/Pict/Operator w/H3 2.0 FeelSafe 3-Wide Casement Transom (This product NOT approved for use in Dade County)	119.5"x99" (31.25"/57"/31.25"x72" w/31.25"/57"/31.25"x28" Transom) (Qualifies 1-Wide 2-High, 2-Wide 2-High, 3-Wide 2-High) Requires 1/4" Steel Horizontal Mull Plate and Mull Clips	+50-60 Wind Zone 3, Missile Level D	436-H-660.73 FL21966.2, 23008 & 23011	Oper & Transoms Type LL or Type NN Picture Type MM or Type OO
H3 2.0 FeelSafe Casement Operator/Pict/Operator (This product NOT approved for use in Dade County)	119.5"x72" (31.25"/57"/31.25"x72") (Qualifies 1-Wide, 2-Wide, 3-Wide) Requires Mull Clips	+50-60 Wind Zone 3, Missile Level D	436-H-660.76 FL21966.3, FL23008 & FL23011	Operator Type LL or Type NN Picture Type MM or Type OO
H3 2.0 FeelSafe 3-Wide Casement Transom (This product NOT approved for use in Dade County)	119.5"x28" (31.25"/57"/31.25"x28") (Qualifies 1-Wide, 2-Wide, 3-Wide) Requires Mull Clips	+50-60 Wind Zone 3, Missile Level D	436-H-660.79 FL21965.1 & FL23011	Type LL or Type NN
H3 2.0 FeelSafe Awning 2-Wide w/1-Wide Picture Transom (This product NOT approved for use in Dade County)	95"x80" (48x36 Call Out w/44" Tall Picture Transom) Requires 1/4" Alum Horizontal Mull Plate and Mull Clips	+50-60 Wind Zone 3, Missile Level D	436-H-659.25 FL21955.1, FL23010 & FL23011	Awning Type LL or Type NN Picture Type MM or Type OO
H3 2.0 FeelSafe Awning 2-Wide (This product NOT approved for use in Dade County)	95"x36" (48x36 Call Out) (Qualifies 1-Wide & 2-Wide) Requires Mull Clips	+50-60 Wind Zone 3, Missile Level D	436-H-659.25 FL21955.1 & FL23010	Type LL or Type NN
H3 2.0 FeelSafe Awning w/ Picture Transom (This product NOT approved for use in Dade County)	48"x108" (48x36"/48x72 Picture Transom) Requires 1/4" Alum Horizontal Mull Plate and Mull Clips	+50-60 Wind Zone 3, Missile Level D	436-H-659.28 FL21955.2, FL23010 & FL23011	Awning Type LL or Type NN Picture Type MM or Type OO
H3 2.0 FeelSafe 1-Wide or 2-Wide Double Hung (This product NOT approved for use in Dade County)	48"x84" (Qualifies Multi-Wide) Requires 1/4" Alum Vertical Mull Plate and Mull Clips	+50-60 Wind Zone 3, Missile Level D	436-H-671.63 FL21907	Type LL or Type NN
H3 2.0 FeelSafe 3-Wide Double Hung w/H3 2.0 FeelSafe 3-Wide Double Hung Transom (This product NOT approved for use in Dade County)	106"x99" (36x72/36x28 Call Out) (Qualifies 1-Wide, 2-Wide, 3-Wide) Requires 1/4" Alum Horizontal Mull Plate and Mull Clips	+50-60 Wind Zone 3, Missile Level D	436-H-671.59 FL21907 & FL21908	Type LL or Type NN
H3 2.0 FeelSafe 3-Wide Double Hung (This product NOT approved for use in Dade County)	106"x72" (36"x72" Call Out) (Qualifies 2-Wide & 3-Wide) Requires Mull Clips	+50-60 Wind Zone 3, Missile Level D	436-H-671.59 FL21907	Type LL or Type NN
H3 2.0 FeelSafe 3-Wide Double Hung Transom (This product NOT approved for use in Dade County)	106"x28" (36"x28" Call Out) (Qualifies 1-Wide, 2-Wide, 3-Wide) Requires Mull Clips	+50-60 Wind Zone 3, Missile Level D	436-H-671.59 FL21907 & FL21908	Type LL or Type NN
H3 2.0 FeelSafe 3-Wide Double Hung/Picture/Double Hung w/H3 2.0 FeelSafe 3-Wide Double Hung Transom (This product NOT approved for use in Dade County)	120"x99" (31.25"/57"/31.25"x71.5" w/31.25"/57"/31.25"x27.5" Transom) (Qualifies 1-Wide 2-High, 2-Wide 2-High, 3-Wide 2-High) Requires 1/4" Alum Horizontal Mull Plate and Mull Clips	+50-60 Wind Zone 3, Missile Level D	436-H-671.56 FL21907 & FL21908	DH & Transom Type LL or Type NN Picture Type MM or Type OO
H3 2.0 FeelSafe 3-Wide Double Hung/Picture/Double Hung (This product NOT approved for use in Dade County)	120"x72" (31.25"/57"/31.25"x71.5") Requires Mull Clips	+50-60 Wind Zone 3, Missile Level D	436-H-671.56 FL21907 & FL21908	DH Type LL or Type NN Picture Type MM or Type OO
H3 2.0 FeelSafe 3-Wide Double Hung Transom (This product NOT approved for use in Dade County)	120"x28" (31.25"/57"/31.25"x27.5") Requires Mull Clips	+50-60 Wind Zone 3, Missile Level D	436-H-671.56 FL21908	Type LL or Type NN
H3 2.0 FeelSafe Double Hung Picture w/Transom (This product NOT approved for use in Dade County)	57.25"x99" (57.25"x72" w/57.25"x27.25" Transom) Requires 1/4" Alum Horizontal Mull Plate and Mull Clips	+50-60 Wind Zone 3, Missile Level D	436-H-671.56 FL21907	DH Type LL or Type NN Picture Type MM or Type OO



	<i>Sizes/Configurations Approved</i>	<i>DP Rating</i>	<i>Approval #</i>	<i>Glazing Options</i>
H3 2.0 2-Wide Double Hung Picture (This product NOT approved for use in Dade County)	93"x72" (57.25/35.5"x72") Requires Mull Clips	+50/-60 Wind Zone 3, Missile Level D	436-H-674.11 FL21908	Type MM or Type OO
H3 2.0 Double Hung Picture (This product NOT approved for use in Dade County)	57.25"x72" Require Mull Clips	+50/-60 Wind Zone 3, Missile Level D	436-H-674.11 436-H-671.56 FL21908	Type MM or Type OO
Clad Energy Saver French Sliding Patio Door (This product NOT approved for use in Dade County)	16-0x8-0 (40"x82-1/4" glass size) Qualifies OXXO	+50/-50 Wind Zone 3, Missile Level D	436-H-649.27-.29 FL# 21440.2	Glass Type DD [1.04" Insul-6mm Temp Interior Lite; .438" Air Space; 8.6mm Annealed Lami (3mm AN; .090" PVB; 3mm AN Ext. Lite)]

Glazing Options:
 Type DD (1.04" Insul--3mm AN/.090" PVB; 3mm AN; .438" Air Space; 6mm Temp Int Lite
 Type LL (1" Insul--3.1mm AN/.090"PVB/3.1mm AN; 13mm XL Edge Spacer; 3.1mm AN Int Lite
 MM (1" Insul--3.9mm An/.090"SGP/3.9mm An; 9.8mm XL Edge Spacer; 4.7mm AN Int Lite
 Type NN (1" Insul--3.1mm AN/.090"PVB/3.1mm AN; 13mm XL Edge Spacer; 3.1mm Tempered Int Lite
 Type Type OO (1" Insul--3.9mm AN/.090"SGP/3.9mm AN; 9.8mm XL Edge Spacer; 4.7mm Tempered Int Lite

